

For More Information

PT Ferindo Energi Instrumen

www.feitech.id

Call us at : 0882-1077-5661



For More Information

PT Ferindo Energi Instrumen

www.feitech.id

Call us at : 0882-1077-5661

The brochure is divided into three main sections: GEAR, BODY, and OUTPUT.

- GEAR:** Shows a close-up of the internal gear assembly. Text: "The material of gear is PPS plastic light weight and Wear-resistant".
- BODY:** Shows the exterior body of the flow meter. Text: "The body material is Aluminium alloy It's not easy to rust and with light weight". Below it, a dimension line indicates "1";1.5";2" Diameter Thread connection".
- OUTPUT:** Shows the electronic output module. Text: "The oqm flow meter without display and with signal output the output is 4-20mA or pulse output". Below it, two options are shown: "01 4-20mA" and "02 PULSE".

OVALGEARFLOWMETER

1. Pengukur aliran rotor positif oval Seri OGM akan mengukur cairan dengan viskositas tinggi atau bervariasi.
2. Rotor bisa tahan dalam tekanan tinggi dan tersedia dalam PPS aluminium.
3. Meter dapat dilengkapi dengan totalisir mekanik yang harganya sangat ekonomis atau layar LCD yang dapat dipasang di bagian atas flow meter sebagai counter.
4. Rotor cocok untuk berbagai macam bahan bakar, minyak dan bahan kimia.

For More Information

PT Ferindo Energi Instrumen

www.feitech.id

Call us at : 0882-1077-5661

5. Anda dapat memasang flow meter OGM baik secara horizontal maupun vertikal. Sangat dianjurkan juga untuk memakai saringan saat instalasi flow meter OGM karena partikel-partikel bersifat kotor maupun tajam bisa merusak poros gear flow meter ini.

MODEL	OGM-25	OGM-40	OGM-50
Ukuran	25mm	40mm	50mm
Arus Minimal	20 Lpm	25 Lpm	30 Lpm
Arus Maksimal	120 Lpm	250 Lpm	300 Lpm
Akurasi	+/- 0.5%	+/- 0.5%	+/- 0.5%
Pengulangan Akurasi	<0.03%	<0.03%	<0.03%
Kekentalan Maksimum	1000cps	1000cps	1000cps
Tekanan	0.3 Mpa	0.3 Mpa	0.3 Mpa



For More Information

PT Ferindo Energi Instrumen

www.feitech.id

Call us at : 0882-1077-5661

